

YOI-4G/LTE

Tiny and Low Power Router
With Integrated 4G/LTE Modem
For Mobile Networking.

4G LTE

35mm

85mm

105mm

≈ 5W

The Internet of Edges (IoE) is a disruptive digital infrastructure created by a network of interconnected edge devices that share resources to deliver high-performing, locally hosted digital services. Autonomous and interoperable, it serves as both an alternative and a complement to centralized global systems. IoE combines cutting-edge technologies in direct communications networking, edge computing, and distributed systems through GreenSoft, designed to integrate custom edge devices. We also offer ready-to-use edge devices called YOI (Your Own Internet of Edges device) with GreenSoft integrated.

YOI-4G/LTE

YOI-4G/LTE is an embedded Linux device equipped with Green Communications' software (GreenSoft). Each device comes with one Wi-Fi 4 interface (2.4 and 5 GHz) that creates a wireless backhaul network with other YOIs and provides an access point Wi-Fi devices. YOI-4G/LTE integrates a 4G/LTE modem to connect a group of YOI to an external network such as private LTE and public 4G. In this case, the edge traffic stays local and global traffic is sent across the gateways to other networks. The device features a web server offering edge services, and applications to users.

■ Turn It On, It Works

Anyone can create a stand-alone digital infrastructure simply by switching on a group of YOI devices. They integrate everything needed to provide connectivity and digital services autonomously, without the need for Internet access or external infrastructure.

■ Mobility

The Internet of Edges supports the mobility of YOI devices, servers and users. Embedded YOI devices collectively form a dynamic, self-configuring wireless network. Users can seamlessly handover from one device to another while maintaining continuity of service.

■ Performance

Technological advances in the Internet of Edges (IoE) offer robustness, energy efficiency, and scalability, making it an alternative and interoperable solution to traditional centralized digital infrastructures. IoE is capable of efficiently handling communications at various scales, whether on a site, city, or regional level

■ Openness

YOI devices provide tools, raw data and support open standards, allowing you to create new edge services, integrate third-party ones, and operate YOI devices like any ordinary Linux system.

YOI-4G/LTE

Tiny and Low Power Router
With Integrated 4G/LTE Modem
For Mobile Networking.

4G LTE

35mm

85mm

105mm

≈ 5W



- 4G/LTE**
- 1 LTE/4G interface – Category 4 - LTE Bands: B1 (FDD 2100), B2 (FDD 1900), B3 (FDD 1800), B4 (FDD 1700 / AWS), B5 (FDD 850), B7 (FDD 2600), B8 (FDD 900), B12 (FDD 700ac), B13 (FDD 700c), B18 (FDD 800), B19 (FDD 800), B20 (FDD 800DD), B25 (FDD 1900), B26 (FDD 850), B28 (FDD 700), B34 (TDD 2000), B38 (TDD 2600), B39 (TDD 1900), B40 (TDD 2300), B41 (TDD 2500), B66 (FDD 1700 / AWS-3)

- Ethernet**
- 1 Ethernet port (10/100/1000 Mbit/s)

- Wi-Fi**
- 1 Wi-Fi interfaces (a, b, g, n)

- Suggested operation**
- Wi-Fi 1: Backhaul
 - 4G/LTE: Other Network Gateway
 - Ethernet: Access

- Frequency**
- 2.4 GHz and 5 GHz

- Antenna**
- 2 Wi-Fi (RP-SMA, 5 dBi max)
 - 2 wide-band 4G/LTE (SMA, 5 dBi max)

- Wireless rates**
- Up to 300 Mbit/s

- Encryption**
- WPA2/WPA3 (access) , SAE (backhaul)

- Operating system**
- Custom Linux system (based on Buildroot)

- CPU**
- Cortex-A9 800 MHz Dual Core

- RAM**
- 512 MB

- Other Interfaces**
- 1 USB OTG, 1 Micro-HDMI

- Environmental features**
- -40°C +85°C

- Dimensions**
- Approx. 85 × 105 × 35 mm (casing without antenna)

- Power supply**
- Power through Ethernet (passive PoE) or Barrel Jack DC from 8 to 60 V (AC adapter included)

- Power Consumption**
- ≈ 5 W

- Weight**
- 320 g (enclosure and antennas included)

- Software**
- Each YOI comes with a GreenSoft license